

One Design Sloop "D" Class

Specifications and Limitations

Barnegat Bay

C.D. Kover, N.A.

<u>Hull</u>		<u>Allowed variations</u>	
		Under	Over
	Length over all.....	18' 9"	18'
	Beam at Deck.....	6' 7"	6' 7/4"
	Planking material optional 1/2" thick	No	Yes
	Frames..7/8" x 7/8" spaced 6" apart	No	Yes
	Keel, Oak or Mahogany, 3" x 10" Amidships.....	No	Yes
	C.B. Trunk Bed pieces, material optional	No	Yes
	Clamp 1" x 2"	No	Yes
	Bilge Stringer, Material optional 1x2"	No	Yes
	Deck beams..Material optional	No	Yes
	Deck 1/2" thick, canvas covered - Material optional	No	Yes
<u>Cockpit</u>	Length 9' 1 1/2" as per plans		
	Side decks, minimum width 1 1/2"	No	Yes
	Cockpit floor, 1/2" thick.....	No	Yes
	Cockpit coaming, 7/16" thick..	No	Yes
<u>Centerboard</u>	Steel plate, 3/16" thick, galv. size, as per plans.	No	Yes
<u>Builder</u>	Wood material optional, size as per plans.		
<u>Masts</u>	Mast to be solid, 5/8" diam round section Rectangular masts of 3/4" material and not less than 3/4" diameter permitted. Rotating masts not permitted. Height of mast from deck to top of main halyard sheave not to exceed 26' 9" Height to jib stay not to exceed 19' Center of mast from face to stem 7' 2" may be shifted to balance, not more than 2" at deck. Main boom to be solid, round or "T" section. Length from aft side of mast to end 18' 0" Foot of sail not to exceed 12' 5" must be fastened to boom for entire length. Roller reef gears permitted.		
<u>Rigging</u>	Masts to have one shroud only on either side and one jib stay. No spreaders permitted. Each stays optional. Details of rigging and fittings optional.		

Sails not to exceed the following dimensions:

Main-sail, hoist, 24'0" Foot 12'6" Leach 25'0"
Battens, three not to exceed 50" in length

Jib, Hoist 17'4" Foot 7'6" Leach 15'3"
Jib to be loose footed and to not on jib stay.

Spinnaker: Tack to Clew 19'0" Leaches 19'0"
Spinnaker Boom limited to 9'0" in length
Spinnaker may be used as Gagne Jib.

A new boat may have two suits of sails the first year.

Restricted to one suit of racing sails of best Egyptian Sail Cloth for Main-sail and Jib.
Must be McJellands #40

Spinnaker shall be of 3.15oz Egyptian sail cloth
Must be McJelland's #40.

Restricted to one suit of working sails of not less than 6oz material. Must be McJelland's.

All boats are restricted to one new suit of racing sails every two years, i.e. to the beginning of the third racing year.

Racing number and class emblem must be on the main-sail.

Equipment

Anchor weighing not less than 15 pounds.
Anchor cable not less than fifty feet of 1/2" diam.

Ballast

No inside ballast permitted.

Crew

Limited to three persons when racing and maximum of four.

Measurement

Any complaint filed by any one racing against a boat as to measurement, or violation of sail measurement, the said owner shall bring his boat and sails for measurement by the committee and shall pay cost of measuring.

Age limit of Class:- 18 years

Bottom paint:-

All boats shall be painted with soft copper

Hauling out:-

May be hauled out at anytime for cleaning.

One Design Sloop.

(C.B. Number B.A.)

Class racing name: "C" Class.

Racing rules: Racing of this class shall be under the N.A.Y.C. rules, and subject to the N.A.Y.C.A. rules not in conflict with the N.A.Y.C.A.

When a member of any other club belonging to the N.A.Y.C.A. shall own a "C" Class Sloop, the said club shall appoint a member to this committee.

Trophy award: Perpetual award, trophy presented by H.B. Hoffman, Governor of N.Y. shall be raced for each year.

Committee governing the "C" Class shall consist of:

Chairman: W.F. Coverley-Smith	N.Y.C.
J.A. DeCamp	N.Y.C.
F.M. Rose	N.Y.C.
C.A. Schroeder	N.Y.C.